

## EdgeSwitch 18X

Ideal for larger-scale WISP applications, the EdgeSwitch® 18X is an affordable high-performance switch with SFP ports and a fanless design. Sixteen Gigabit RJ45 ports offer copper connectivity with PoE input on port 1 and PoE passthrough on port 16. Two SFP ports offer fiber connectivity.



### EdgeSwitch® 18X

## Mechanical

---

**Dimensions** 299.8 x 160 x 43.7 mm (11.8 x 6.3 x 1.7")

---

**Weight** Without Mount: 1.15 kg (2.54 lb)  
With Mount: 1.43 kg (3.15 lb)

---

**Enclosure Material** Metal

---

**Mount Material** Metal

---

## Hardware

---

**Total Non-Blocking Throughput** 18 Gbps

---

**Switching Capacity** 36 Gbps

**Forwarding Rate** 26.78 Mpps

---

**Max. Power Consumption** 14W (Excludes PoE Output)

---

**ESD/EMP Protection** Air:  $\pm 16$  kV, Contact:  $\pm 8$  kV

---

**Power Method** External AC/DC Adapter  
24V Passive PoE

---

**Power Supply** 24VDC, 1.0A Power Adapter (Included)  
24V Passive PoE

---

**Supported Voltage Range** 9 - 30VDC

---

**Networking Interfaces** (16) 10/100/1000 Mbps Ethernet RJ45 Ports  
(2) 1 Gbps SFP Ports

---

**PoE Interfaces** (1) 24V Passive PoE Port (Pins 4, 5+; 7, 8-)

---

**Management Interface** Ethernet In-Band

---

**Passive PoE Max Wattage per Port** 15W

---

**Passive PoE Voltage Range** 24V

**Operating Temperature** -10 to 50° C (14 to 122° F)

---

**Operating Humidity** 10 - 90% Noncondensing

---

**Certifications** CE, FCC, IC

---

## LEDs

---

**System** (1) White/Blue

---

**Ethernet** Green: 1G, Amber: 10/100 Mbps

---

**SFP** Green: 1G

---

## Software

---

**Mode** Layer 2 Ethernet Switch

---

**VLAN** 4K VLANs

---

**QoS** (16) Priority Queues per User Port and Traffic Classification

---

**Jumbo Frame** 10 KB

**PoE** Enable/Disable Passive PoE

---

**Other** TFTP Recovery

---

**Ubiquiti Specific Features** Ubiquiti Discovery

---

**Minimum Software Requirements** Web Browser (Chrome Recommended)

