



PPISM Station™ AC

Shielded airMAX® ac Radio Base
with airPrism® Technology

Model: PS-5AC

Proprietary Ubiquiti® airMAX ac Processor

airPrism Active RF Filtering Technology

Dedicated Wi-Fi Radio for Management

Overview

Ubiquiti Networks launches the PrismStation™ 5AC, featuring airPrism technology and dedicated Wi-Fi management.

Improved Noise Immunity

The PrismStation 5AC directs RF energy in a tighter beamwidth using an interchangeable isolation antenna horn, available in both symmetrical and asymmetrical designs. Compatible antennas* include the following:

- PrismAP-5-30
- PrismAP-5-45
- PrismAP-5-60
- PrismAP-5-90

With the focus in one direction, the PrismStation 5AC blocks or spatially filters out noise, so noise immunity is improved. This feature is especially important in an area crowded with other RF signals of the same or similar frequency.

Modular Design

With flexible sectorization for optional antenna beamwidths, the horn antenna is interchangeable and improves beam-shaping for specific deployment and environment needs. The PrismStation 5AC uses horn antenna sectors designed for increased co-location performance without sacrificing gain.

Providing high throughput and an innovative form factor, the PrismStation 5AC is versatile and cost-effective to deploy. The PrismStation 5AC also utilizes the latest ESD protection to help protect against power surges.

Scalability

Symmetrical horn antennas (30° and 45° versions, models PrismAP-5-30 and PrismAP-5-45, respectively) offer breakthrough scalability options for wireless systems. Unique beam performance and great co-location characteristics allow for a higher density of sectors than traditional sector technology.


Enhanced Co-Location

Asymmetrical horn antennas (60° and 90° versions, models PrismAP-5-60 and PrismAP-5-90, respectively) have naturally attenuated side lobes and extremely low back radiation. They offer the best front-to-back ratio in the industry and the lowest side lobe radiation. Asymmetrical horn antennas are ideal for cluster sector installations with high co-location requirements.

* Antennas not included with the PS-5AC.


Application Examples

PtMP Client Links




The PrismStation 5AC acts as the AP communicating with the NanoBeam ac CPEs in an airMAX PtMP network.

PtP Link



Use a PrismStation 5AC on each side of a PtP link.

Beam Performance Perfected



Software

airOS®8

Sporting an all-new design for improved usability, airOS® v8 is the revolutionary operating system for Ubiquiti® airMAX ac products.

Powerful Wireless Features

- Access Point PtMP airMAX Mixed Mode
- airMAX ac Protocol Support
- Long-Range Point-to-Point (PtP) Link Mode
- Selectable Channel Width
 - PtP: 10/20/30/40/50/60/80 MHz
 - PtMP: 10/20/30/40 MHz
- Automatic Channel Selection
- Transmit Power Control: Automatic/Manual
- Automatic Distance Selection (ACK Timing)
- Strongest WPA2 Security

Usability Enhancements

- airMagic® Channel Selection Tool
- Dynamic Configuration Changes
- Instant Input Validation
- Redesigned User Interface
- HTML5 Technology
- Optimization for Mobile Devices
- Detailed Device Statistics
- Diagnostic Tools, including RF Diagnostics, and airView® Spectrum Analyzer


UMobile App

The PrismStation 5AC integrates a separate Wi-Fi radio for fast and easy setup using your mobile device.


Accessing airOS via Wi-Fi

The U®Mobile App provides instant accessibility to the airOS configuration interface and can be downloaded from the App Store (iOS) or Google Play™ (Android). UMobile allows you to set up, configure, and manage the PrismStation 5AC and offers various configuration options once you're connected or logged in.


Dashboard



System Settings



UMobile Configuration



Advanced RF Analytics

airMAX ac devices feature a multi-radio architecture to power a revolutionary RF analytics engine.

An independent processor on the PCBA powers a second, dedicated radio, which persistently analyzes the full 5 GHz spectrum and every received symbol to provide you with the most advanced RF analytics in the industry.

Real-Time Reporting

airOS 8 displays the following RF information:

- Persistent RF Error Vector Magnitude (EVM) constellation diagrams
- Carrier to Interference-plus-Noise Ratio (CINR) histograms
- Signal-to-Noise Ratio (SNR) time series plots

Spectral Analysis

airView allows you to identify noise signatures and plan your networks to minimize noise interference. airView performs the following functions:

- Constantly monitors environmental noise
- Collects energy data points in real-time spectral views
- Helps optimize channel selection, network design, and wireless performance


airView runs in the background without disabling the wireless link, so there is no disruption to the network.

In airView, there are three spectral views, each of which represents different data.


- **Waterfall** Aggregate energy collected for each frequency
- **Waveform** Aggregate energy collected
- **Ambient Noise Level** Background noise energy shown as a function of frequency

airView provides powerful spectrum analyzer functionality, eliminating the need to rent or purchase additional equipment for conducting site surveys.


Multi-Radio Architecture




Constellation Diagrams



SNI Diagram and CINR Histogram



Dedicated Spectral Analysis



Technology



Unlike standard Wi-Fi protocol, Ubiquiti's Time Division Multiple Access (TDMA) airMAX protocol allows each client to send and receive data using pre-designated time slots scheduled by an intelligent AP controller.

This time slot method eliminates hidden node collisions and maximizes airtime efficiency, so airMAX technology provides performance improvements in latency, noise immunity, scalability, and throughput compared to other outdoor systems in its class.

Intelligent QoS Priority assigned to voice/video for seamless streaming.

Scalability High capacity and scalability.

Long Distance Capable of high-speed, carrier-class links.

Superior Performance

The next-generation airMAX ac technology boosts the advantages of our proprietary TDMA protocol.


Ubiquiti's airMAX engine with custom IC dramatically improves TDMA latency and network scalability. The custom silicon provides hardware acceleration capabilities to the airMAX scheduler, to support the high data rates and dense modulation used in airMAX ac technology.

Throughput Breakthrough

airMAX ac supports high data rates, which require dense modulation: 256QAM – a significant increase from 64QAM, which is used in airMAX.


With their use of proprietary airMAX ac technology, airMAX ac products support up to 500+ Mbps real TCP/IP throughput – up to triple the throughput of standard airMAX products.

airMAX ac TDMA Technology




Up to 100 airMAX ac stations can be connected to an airMAX ac Sector; four airMAX ac stations are shown to illustrate the general concept.

airMAX Network Scalability



Superior Throughput Performance



Technology

airPRISM[®]

To enhance airMAX ac performance, Ubiquiti Networks introduces our patented airPrism technology, which is featured on the PrismStation 5AC, model PS-5AC.

Improves SNR

High data rates require a high Signal-to-Noise Ratio (SNR), which is challenging to achieve, especially in noisy, high-density areas.

Integrated into Ubiquiti's custom silicon, airPrism technology creates a high SNR by isolating signals within the operating channel and rejecting interference using the specialized circuitry of the High-Selectivity Receiver (HSR).

Removes Interference

Depending on the product model and operating mode, available channel widths may include 10, 20, 30, 40, 50, 60, and/or 80 MHz.

Theoretically, APs operate on different channels; however, because of the wider channel bandwidths, there can be overlap in spectrum usage.

airPrism technology removes up to an additional 30+ dB of adjacent channel interference through the active filtering design, so an airMAX ac AP with airPrism technology can provide significantly greater performance than a typical AP.

Facilitates AP Co-Location


Co-location is vital in many scenarios. For example, a WISP may have limited tower space, so it must co-locate all APs within that allotted footprint. Shielding and other means can lessen interference but may be impractical.

By deploying airMAX ac APs with airPrism technology, you can co-locate APs and enhance the overall performance of your wireless network.


| Number of APs | Channel Width |
|---------------|---------------|
| 4 | 80 MHz* |
| 8 | 40 MHz |
| 16 | 20 MHz |

* PtP only

Active Radio Frequency Filtering



Improved Latency and Noise Immunity




Modular Design

Interchangeable Antennas

The PrismStation 5AC is compatible with 4 different isolation antennas (not included). Each antenna is designed with a precise radiation angle for specific beam shaping, ranging from 30° to 90°, making them suitable for a wider range of installations.

- Asymmetrical horn antennas designed for increased co-location performance
- Available in 30°, 45°, 60°, and 90° angle designs
- All metal, shielded radio base
- Single button release for ease of changing antennas
- Newly designed horns for improved beam shaping



Hardware Overview

Using airMAX ac technology, the PrismStation 5AC supports up to 500+ Mbps real TCP/IP throughput.

The PrismStation 5AC comes with a mounting bracket that allows for ± 20° tilt adjustments of the horn's elevation. This pole-mounting method allows for easy adjustments depending on your deployment needs.



PrismStation 5AC with PrismAP-5-45 Mounted on Pole

Specifications

| PS-5AC | |
|--------------------------------------|--|
| Dimensions Mounting Hardware Only | 155 x 155 x 104 mm (5.16 x 5.16 x 4.09") 83 x 117 x 69 mm (3.27 x 4.61 x 2.72") |
| Weight Mounting Hardware Only | 770 g (1.70 lb) 790 g (1.74 lb) |
| Networking Interface | (1) 10/100/1000 Ethernet Port |
| RF Connector | (1) GPS* |
| LED | Power |
| Max. Power Consumption | 10W |
| Power Supply | 24V, 1A Gigabit PoE Adapter (Included) |
| Power Method | Passive PoE (Pairs 4, 5+; 7, 8 Return) |
| Supported Voltage Range | 20 to 26VDC |
| Processor Specs | MIPS 74 Kc |
| Memory | 128 MB DDR2 SDRAM, 16 M NOR FLASH |
| Max. VSWR | 2:1 |
| Polarization | Dual-Linear |
| Wind Loading | 31 N @ 200 km/h (7 lbf @ 125 mph) |
| Wind Survivability | 200 km/h (125 mph) |
| Operating Temperature | -40 to 70° C (-40 to 158° F) |
| Operating Humidity | 5 to 95% Noncondensing |
| Mounting | Pole-Mount (Kit Included) |
| ESD/EMP Protection | ± 24 kV Contact/Air |
| Certifications | FCC, IC, CE |

* Reserved for future use

| Operating Frequency (MHz) | | |
|---------------------------|-------------------------|-------------------------|
| Worldwide | 5150 - 5875 | |
| USA | U-NII-1: 5150 - 5250 | U-NII-3: 5725 - 5850 |

| Management Radio (MHz) | |
|------------------------|-------------|
| Worldwide | 2412 - 2472 |
| USA | 2412 - 2462 |

| PS-5AC Output Power: 28 dBm | | | | | | | |
|-----------------------------|---------------|---------|-----------|-------------------------|---------------|-------------|-----------|
| TX Power Specifications | | | | RX Power Specifications | | | |
| Modulation | Data Rate | Avg. TX | Tolerance | Modulation | Data Rate | Sensitivity | Tolerance |
| airMAX ac | 1x BPSK (½) | 28 dBm | ± 2 dB | airMAX ac | 1x BPSK (½) | -96 dBm | ± 2 dB |
| | 2x QPSK (½) | 28 dBm | ± 2 dB | | 2x QPSK (½) | -95 dBm | ± 2 dB |
| | 2x QPSK (¾) | 28 dBm | ± 2 dB | | 2x QPSK (¾) | -92 dBm | ± 2 dB |
| | 4x 16QAM (½) | 28 dBm | ± 2 dB | | 4x 16QAM (½) | -90 dBm | ± 2 dB |
| | 4x 16QAM (¾) | 28 dBm | ± 2 dB | | 4x 16QAM (¾) | -86 dBm | ± 2 dB |
| | 6x 64QAM (⅔) | 28 dBm | ± 2 dB | | 6x 64QAM (⅔) | -83 dBm | ± 2 dB |
| | 6x 64QAM (¾) | 27 dBm | ± 2 dB | | 6x 64QAM (¾) | -77 dBm | ± 2 dB |
| | 6x 64QAM (⅘) | 26 dBm | ± 2 dB | | 6x 64QAM (⅘) | -74 dBm | ± 2 dB |
| | 8x 256QAM (¾) | 24 dBm | ± 2 dB | | 8x 256QAM (¾) | -69 dBm | ± 2 dB |
| | 8x 256QAM (⅘) | 22 dBm | ± 2 dB | | 8x 256QAM (⅘) | -65 dBm | ± 2 dB |

Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at: www.ubnt.com/support/warranty
 ©2017 Ubiquiti Networks, Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, airMagic, airMAX, airOS, airPrism, airView, and PrismStation are trademarks or registered trademarks of Ubiquiti Networks, Inc. in the United States and in other countries. The App Store is property of Apple. Google, Android, and Google Play are the property of Google. All other trademarks are the property of their respective owners.



www.ubnt.com