

UniFi[®] Network



UniFi LTE Pro

Third-Party SIM Card Support.

Avoid internet downtime and lost productivity by adding a UniFi LTE Pro to your existing UniFi network.

UniFi LTE Pro provides backup cellular internet connectivity to ensure your UniFi WAN network is always running. This model works in the EU region and supports European LTE and WCDMA bands. It has a Nano SIM card slot for your own card. Insert the Nano SIM, connect to any switch port in your corporate network, and activate the device.



Mechanical

Dimensions	66 x 202 x 32 mm (2.60 x 7.96 x 1.27")
Weight	Without Stand: 223 g (7.86 oz) With Stand: 336 g (11.85 oz)
Enclosure Material	Polycarbonate
Mount Materials	Stand: Aluminum Wall Mount: Polycarbonate

Hardware

Processor	74 Kc MIPS Processor at 775 MHz
Memory Information	128 MB DDR2
Management Interface	Ethernet
Networking Interfaces	(2) 10/100/1000 Mbps RJ45 Port WP7607 LTE
SIM	Nano-SIM
LTE Bands	CAT4, B1/3/7/8/20/28
LCM Display	1.54" Screen
Power Method	802.3at PoE, Passive PoE (48V)
Power Supply	802.3at PoE (Pins 1, 2+/3, 6- or 4, 5+/7, 8-)
Supported Voltage Range	44 to 57VDC
Max. Power Consumption	8.5W
Max. TX Power	19 dBm
MIMO	U-LTE 2 x 2 Category 4 LTE Radio
Throughput Speeds	150 Mbps

Antenna Gain	LTE	B1	2 dBi
		B3	1.5 dBi
		B7	2 dBi
		B8	3.5 dBi
		B20	2 dBi
		B28	2 dBi

Button	Factory Reset
Mounting	Wall Mount/Foot Stand (Included)
ESD/EMP Protection	Air/Contact: ± 24 kV
Operating Temperature	-10 to 60° C (-14 to 140° F)



Operating Humidity	5 to 95% Noncondensing
Certifications	CE, FCC, IC



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at www.ui.com/support/warranty

©2020 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, the Ubiquiti beam logo, UniFi, and UniFi Network are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. All other trademarks are the property of their respective owners.